

LANDSTAR™ LS455EFI

LS455EFI UTILITY VEHICLE SPECIFICATIONS

POWER	429cc LandMAXX Commercial Power Kohler EFI air-cooled OHV single cylinder
SPEED	Up to 22 mph*
FUEL CONSUMPTION	Up to 20 mpg*
RANGE	Up to 100 miles*
STARTING	12V keyed ignition with recoil backup
BATTERY	12V / 360 cca utility class
SPARK PLUG	NGK BPR6ES
FUEL CAPACITY	5.0 gal
ALTERNATOR	25 amp
TRANSMISSION	CVT automatic
TRANSAXLE	Gear drive Schafer/DANA oil-filled transaxle
DIFFERENTIAL	Locking
DRIVE	2 wheel drive
FRONT SUSPENSION	Double A-arms, adjustable shocks with up to 3" travel
REAR SUSPENSION	Articulated rear swing arm, featuring quad adjustable shocks with up to 3" travel
BRAKE SYSTEM	6.25" dual rear hydraulic drum with hand operated parking brake
TIRES	25 x 8 - 12 (front) 25 x 10 - 12 (rear)
DIMENSIONS	110" L x 49" W x 78" D
WHEEL BASE	73.5"
TURNING RADIUS	7.5' inside radius
DRY WEIGHT	824 lbs.
SHIPPING WEIGHT	1041 lbs.
BED MATERIAL	Structural foam "Poly Bed" with stake pockets
BED DIMENSIONS	35.25" L x 41.5" W x 11" D
BED CAPACITY	9.25 cu.ft. / 400 lbs.
REAR FLIP SEAT	Available as an option
TOWING CAPACITY	1100 lbs.
VEHICLE CAPACITY	900 lbs.
WARRANTY	3 year engine / All other 1 year limited
ADDITIONAL FEATURES	3pt lap/shoulder belts for driver and passenger, twin 12V auxiliary outlets for accessories, 12V/18W LED headlights, polyurethane powder paint, 2" rear receiver hitch, dump bed, bench seating, welded steel frame, headrests, under seat storage



Specifications are subject to change without notice.

* Estimates. Actual top speeds, fuel consumptions and vehicle ranges may vary due to driving conditions, terrain, climate and other extenuating circumstances.



800-643-7332 ★ AmericanLandMaster.com ★ USA