

LANDSTAR™ CREW2

CREW2 UTILITY VEHICLE SPECIFICATIONS

POWER	674cc LandMAXX Commercial Power Engine by Kohler Command Pro® CH640 rated at 20.5hp 4-stroke OHV V-twin with oil pressure warning light
SPEED	Up to 24 mph*
FUEL CONSUMPTION	Up to 18 mpg*
RANGE	Up to 90 miles*
STARTING	12V keyed ignition with recoil backup
BATTERY	12V / 360 cca utility class
SPARK PLUG	NGK C7HSA
FUEL CAPACITY	5.0 gal
ALTERNATOR	25 amp
TRANSMISSION	CVT automatic
TRANSAXLE	Gear drive Schaefer/DANA oil-filled transaxle
DIFFERENTIAL	Locking
DRIVE	2 Wheel Drive
FRONT SUSPENSION	Double A-arms, adjustable shocks with up to 3" travel
REAR SUSPENSION	Articulated rear swing arm, featuring quad adjustable shocks with up to 3" travel
BRAKE SYSTEM	Hydraulic disc front, hydraulic drum rear with hand operated parking brake
TIRES	25 x 8 - 12 (front) 25 x 10 - 12 (rear)
DIMENSIONS	143" L x 49" W x 76.5" H
WHEEL BASE	104"
TURNING RADIUS	12.25' inside radius
DRY WEIGHT	1210 lbs.
SHIPPING WEIGHT	1210 lbs. (ships uncrated)
BED MATERIAL	Structural foam "Poly Bed" with stake pockets
BED DIMENSIONS	35.25" L x 41.5" W x 11" D
BED CAPACITY	9.25 cu.ft. / 400 lbs.
REAR FLIP SEAT	Available as an option
TOWING CAPACITY	1200 lbs.
VEHICLE CAPACITY	1500 lbs.
WARRANTY	3 year engine / All other 1 year limited
ADDITIONAL FEATURES	3pt lap/shoulder belts for driver and passenger, twin 12V auxiliary outlets for accessories, 12V/18W LED headlights, polyurethane powder paint, 2" rear receiver hitch, dump bed, bench seating, welded steel frame, headrests (front & rear), under seat storage (front & rear)



Specifications are subject to change without notice.

* Estimates. Actual top speeds, fuel consumptions and vehicle ranges may vary due to driving conditions, terrain, climate and other extenuating circumstances.

 **AMERICAN
LANDMASTER®**
Making Your Life Easier

800-643-7332 ★ AmericanLandMaster.com ★ 